

# PHE845

- EMI suppressor, class X1, metallized polypropylene
- 0.01 – 1.0  $\mu\text{F}$ , 760 VAC/600VAC, +105°C

## TYPICAL APPLICATIONS

For worldwide use as electromagnetic interference suppressor in all X1 and across-the-line applications.

## CONSTRUCTION

Metallized polypropylene winding, encapsulated in self-extinguishing material meeting the requirements of UL 94 V-0.

## TECHNICAL DATA


<b>Rated voltage</b>	760 VAC 50/60 Hz (ENEC) 600 VAC 50/60 Hz (UL, CSA)	
<b>Capacitance range</b>	0.01 – 1.0 $\mu\text{F}$	
<b>Capacitance tolerance</b>	$\pm 20\%$ standard, $\pm 10\%$ option	
<b>Temperature range</b>	-40 to +105°C	
<b>Climatic category</b>	40/105/56/B	
<b>Approvals</b>	ENEC, UL, CSA	
<b>Dissipation factor</b>	Maximum values at +23°C	
	$C \leq 0.1 \mu\text{F}$	$0.1 \mu\text{F} < C \leq 1 \mu\text{F}$
1 kHz	0.1%	0.1%
10 kHz	0.2%	0.4%
100 kHz	0.6%	-

**Test voltage between terminals** The 100% screening factory test is carried out at 4250 VDC. The voltage level is selected to meet the requirements in applicable equipment standards. All electrical characteristics are checked after the test.

**Resonance frequency** Tabulated self-resonance frequencies  $f_0$  refer to 5 mm lead length.

**Insulation resistance**  $C \leq 0.33 \mu\text{F}$ :  $\geq 30\,000 \text{ M}\Omega$   
 $C > 0.33 \mu\text{F}$ :  $\geq 10\,000 \text{ s}$

**In DC application** Recommended voltage:  $\leq 1500\text{VDC}$



p	d	std l	max l	b
$22.5 \pm 0.4$	0.8	6	30	$\pm 0.4$
$27.5 \pm 0.4$	0.8	6	30	$\pm 0.4$
$37.5 \pm 0.5$	1.0	6	30	$\pm 0.7$

Tolerance in lead length  
 $< 30 \text{ mm}$   $^{+0}_{-1} \text{ mm}$

$30 \text{ mm}$   $^{+5}_{-0} \text{ mm}$

## ENVIRONMENTAL TEST DATA

<b>Endurance</b>	IEC 60384-14	1.25 x $U_R$ VAC 50 Hz, once every hour increased to 1000 VAC for 0.1 s, 1000 h at upper rated temperature	
<b>Vibration</b>	IEC 60068-2-6 Test Fc	3 directions at 2 hours each, 10-55 Hz at 0.75 mm or 98 $\text{m/s}^2$	No visible damage No open or short circuit
<b>Bump</b>	IEC 60068-2-29 Test Eb	1000 bumps at 390 $\text{m/s}^2$	No visible damage No open or short circuit
<b>Change of temperature</b>	IEC 60068-2-14 Test Na	Upper and lower rated temperature 5 cycles	No visible damage
<b>Active flammability</b>	EN 132400		
<b>Passive flammability</b>	IEC 60384-14 (1993) EN 132400 UL1414	Enclosure material of UL94V-0 flammability class	
<b>Humidity</b>	IEC 60068-2-3 Test Ca	+40°C and 90 – 95% R.H.	56 days

## ARTICLE TABLE

Capacitance $\mu\text{F}$	Box code	Max dimensions in mm			$f_o$ MHz	Max $dU/dt$ V/ $\mu\text{s}$	Article code
		B	H	L			
<b>LEAD SPACING 22.5 MM</b>							
0.010	D13	6.5	14.5	26.0	11	100	PHE845VD5100MR06L2
0.015	D13	6.5	14.5	26.0	9.2	100	PHE845VD5150MR06L2
0.022	D13	6.5	14.5	26.0	7.6	100	PHE845VD5220MR06L2
0.033	D17	7.0	16.5	26.0	6.4	100	PHE845VD5330MR06L2
0.047	D15	9.0	18.5	26.0	5.3	100	PHE845VD5470MR06L2
0.068	D18	10.5	19.0	26.0	4.4	100	PHE845VD5680MR06L2
0.10	D16	11.0	21.5	26.0	3.5	100	PHE845VD6100MR06L2
0.15	D20	13.5	23.0	26.0	3.1	100	PHE845VD6150MR06L2
0.22	D19	15.5	24.5	26.0	2.7	100	PHE845VY6220MR06L2*

## LEAD SPACING 27.5 MM

0.10	F11	10.5	20.5	31.5	3.4	100	PHE845VF6100MR06L2
0.15	F12	11.5	22.5	31.5	3.0	100	PHE845VF6150MR06L2
0.22	F03	13.5	23.0	31.5	2.4	100	PHE845VF6220MR06L2
0.33	F15	19.0	29.0	31.5	2.0	100	PHE845VF6330MR06L2
0.47	F16	21.0	30.0	31.5	1.6	100	PHE845VZ6470MR06L2*

## LEAD SPACING 37.5 MM

0.47	R04	15.0	26.0	41.0	1.6	100	PHE845VW6470MR06L2*
0.47	R02	16.5	32.0	41.0	1.6	100	PHE845VR6470MR06L2
0.68	R03	19.0	36.0	41.0	1.2	100	PHE845VR6680MR06L2
1.0	R06	21.0	38.0	41.0	1.0	100	PHE845VW7100MR06L2*

\* Only  $\pm 20\%$ 

## APPROVALS/REFERENCE DOCUMENTS

Certification Body	Specification	Approval reference
ENEC	EN 132400	SE/0140-2
UL	UL 1283 ( $U_R=600$ VAC)	E100117
CSA	C 22.2 No. 8 ( $U_R=600$ VAC)	E100117

## ORDERING INFORMATION

The article code for the standard part is given in the article table.  
For other options, see page 12.

## MARKING

- RIFA
- RIFA article code
- Rated capacitance
- Capacitance tolerance code
- Rated voltage
- X1
- Approval marks
- Manufacturing date code
- IEC climatic category
- Passive flammability class